United States Patent [119]

Banerjee et al.

[11] Patent Number:

4,938,236

[45] Date of Patent: Jul. 3, 1990

[54]	TOBACCO	SMOKING	ARTICLE
------	---------	----------------	---------

[75] Inventors: Chandra K. Banerjee, Pfafftown;

Henry T. Ridings, Lewisville, both of

R. J. Reynolds Tobacco Company, [73] Assignee:

Winston-Salem, N.C.

[21] Appl. No.: 408,814

Sep. 18, 1989 [22] Filed:

[51] Int. Cl.⁵ A24D 1/00; A24D 1/18

[52] U.S. Cl. 131/194; 131/271;

131/273; 131/360

131/360, 359

[56] References Cited

U.S. PATENT DOCUMENTS

2,104,266	1/1938	McCormick .
3,258,015	6/1966	Ellis et all.
3,683,936	8/1972	O'Neil, Jr.
4,079,742	3/1978	Rainer et al.
4,149,548	4/1979	Bradshaw

4,284,089 8/1981 Ray . 4,393,884 7/1983 Jacobs .

4,708,151 11/1987 Shelar.

4,714,082 12/1987. Banerjee et al. ... 4,756,318 7/1988 Clearman et al. .

4,774,971 10/1988 Vieten .

4,793,365 12/1988 Sensabaugh, Jr. et all .

FOREIGN PATENT DOCUMENTS

276250 6/1967 Australia .

86/02528 5/1986 World Int. Prop. O. .


Primary Examiner-V. Millin

[57]

ABSTRACT

A cigarette provides tobacco flavor by heating tobacco, but not burning tobacco or any other material. A heat source which includes granular magnesium, granular iron, and finely divided cellulose generates heat upon contact thereof with an aqueous solution of potassium chloride. The heat source is in a heat exchange relationship with the tobacco. Heat generated by the heat source heats tobacco in a controlled manner. Flavors volatilize from the tobacco and are drawn from the cigarette and into the mouth of the smoker. Typical heat sources heat the tobacco to a temperature within about 70° C. to about 180° C. for 4 to 8 minutes.

47 Claims, 2 Drawing Sheets



RECEIVED:
PHILLIP MORRIS MANAGEMENT CORPLAW DEPT-PATENT SECTION

Source: https://www.industrydocuments.ucsf.edu/docs/psxl0000